



# The Most Versatile Lightweight Vehicle for Insect & Weed Control

SINCE 1967



## High Operator Safety

- Large, Deep, Flexible Cargo Area
- Durable and Dependable
- Low Cost of Ownership
- All Season Operation



## Argo 8x8 XT Models

### APPLICATIONS

- Mosquito Abatement
- Vector & Pest Control
- Sand Fly Reduction
- Efficient Weed Control
- Environmental Studies
- People & Equipment Transport
- Support Vehicle
- Remote Towing

### FEATURES & CAPABILITIES

- Very Low Ground Pressure
- Environmentally Friendly
- Operates in Flooded Areas
- Crosses Deep Mud and Marshy Terrain
- Fully Amphibious\*
- Up to 6 Passengers\*\*
- High Altitude Performance
- Overcomes Obstacles
- Hauls Trailers and Supplies

## EXTREME TERRAIN VEHICLE SOLUTIONS



**Optional Tracks**



**Sand Fly Prevention**



**Salt Water Resistant**



**Low Ground Pressure**



**Customized Sprayers**



**Fully Amphibious**



**Mozzie Larvicide Applicators**



**Mozzie Electric Foggers**



**Mozzie Engine Driven Foggers**

Complete insect abatement solutions at [www.arro-gun.com](http://www.arro-gun.com)

SPECIFICATIONS	CENTAUR 954 DT	ARGO 8x8 XTD	ARGO 8x8 XT1	ARGO 8x8 750 HD1
Engine	34 HP, turbo diesel	24 HP, in-line, 3-cylinder, diesel	30 HP, 4 cycle OHV V-Twin, petrol	30 HP, 4 cycle OHV V-Twin, petrol
Transmission	Automatic	Automatic	Automatic	Automatic
Land Speed	25 mph (40 km/h)	17 mph (27 km/h)	17 mph (27 km/h)	20 mph (32 km/h)
Carrying Capacity	1,500 lbs (680 kg)	1,340 lbs (608 kg) on land 840 lbs (382 kg) in water	1,500 lbs (680 kg) on land 1,000 lbs (454 kg) in water	1,150 lbs (521 kg) on land 1,000 lbs (454 kg) in water
Towing Capacity	2,200 lbs (1000 kg)	2,000 lbs (905 kg)	2,000 lbs (905 kg)	1,800 lbs (816 kg)
Drawbar Pull***	2,400 lbs (1090 kg)	1,800 lbs (816 kg)	1,800 lbs (816 kg)	1,460 lbs (660 kg)
Controls	Automotive-style	Multi-position, one-piece, ergonomic handlebar steering	Multi-position, one-piece, ergonomic handlebar steering	One-piece, ergonomic handlebar steering
Winches	Optional front and rear winches	Optional front and rear winches	Optional front and rear winches	Optional front and rear winches
Under Body	Full, underbody skid plate	Full, underbody skid plate	Full, underbody skid plate	Full, underbody skid plate
Upper Body	Seats 2, full cab enclosed ROPS, versatile rear cargo platform	Seats up to 4 on land or water, ROPS available, versatile rear cargo platform	Seats up to 4 on land or water, ROPS available, versatile rear cargo platform	Seats up to 6 on land / 4 on water, ROPS available

Ground Pressure	FULL LOAD CAPACITY			
with 15" Mud Tracks	2.2 psi (15 kPa)	1.91 psi (13.02 kPa)	1.91 psi (13.02 kPa)	N/A
with 18" Mud Tracks	1.27 psi (8 kPa)	1.06 psi (7.23 kPa)	1.06 psi (7.23 kPa)	0.84 psi (6 kPa)

Please contact us for more details about customized add-on solutions.



Simon Bolivar Cad.19/3-4  
Çankaya / Ankara /Turkey  
Tel: +90 312 441 4104  
Fax: +90 312 441 4108  
[www.gigra.com](http://www.gigra.com) [info@gigra.com](mailto:info@gigra.com)



\*Applies to ARGO 750 HD1 and ARGO XT models. The CENTAUR is not fully amphibious, but can cross water with a fording depth of 26" (660 mm). \*\* Applies to ARGO 750 HD1. \*\*\* Drawbar Pull ratings based on ISO 7464-1983. Some vehicle applications shown are for demonstration purposes, originating from third parties and not available from ARGO. In all cases, vehicle load limits have been considered. For safety, always wear approved helmets and eye protection. When operating in water, always wear approved Personal Floatation Devices. Always remain seated while in the ARGO. 678-16 • Printed in Canada 07/2013